

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)


PCT

(10) International Publication Number
WO 2005/005993 A1

- (51) International Patent Classification⁷: **G01P 3/80**, B60T 8/00
- (21) International Application Number: PCT/EP2003/007282
- (22) International Filing Date: 7 July 2003 (07.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **NIRA DYNAMICS AB** [SE/SE]; Teknikringen 1 F, 58330 Linköping (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **GUSTAVSSON, Fredrik** [SE/SE]; Farskinnsvägen 19, S-586 66 Linköping (SE). **NILSSON, Jonas** [SE/SE]; Norgegatan 18, S-582 31 Linköping (SE). **GUSTAVSSON, Tony** [SE/SE]; Gustavsbergsgatan 8, S-431 37 Mölndal (SE).
- (74) Agents: **JACOBY, Georg** et al.; SAMSON & PARTNER, Widenmayerstr. 5, 80538 München (DE).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: METHOD AND SYSTEM OF DETERMINING THE ABSOLUTE VELOCITY OF A VEHICLE



(57) Abstract: A method of determining the velocity (v) of a vehicle is provided. The vehicle has at least one pair of a front and a rear wheel which are spaced by a wheel spacing (B). Front and rear wheel speed signals (ω) are determined which are indicative of the time dependent behavior of the front and rear wheel speeds, respectively. The front and rear wheel speed signals (ω) are correlated in order to determine a specific correlation feature indicative of the time delay (τ) between the front wheel and rear wheel speed signals. The velocity (v) of the vehicle is determined based on said correlation feature and the wheel spacing (B).

WO 2005/005993 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.